

**Product information**

<b>Product description:</b>	SOLL GLASS is two component fiberglass putty. Easy to work and sand even with a coarse sanding paper (P120 - P150). Can be used under filler directly. Manual / machine sanding dry. Easy to work also with homogenous surfaces even by applying thick coats. Doesn't fill the sanding paper and has very good adhesion to surface. It can be used to reinforce damaged surfaces.
<b>Physical characteristics:</b> <b>Color:</b> <b>Density:</b>	Green 1,75 g / cm <sup>3</sup>
<b>Substrates and application:</b>	SOLL GLASS was designed for use on steel, aluminium and glass-fibre reinforced plastic. The surface must be cleaned, dry, degreased and matted.
<b>Mixing ratio:</b>	Thoroughly mix putty and 2-3% of hardener (by weight): Putty           100 g Hardener      2-3 g
<b>Body filling:</b>	3 – 5 min.
<b>Pot life:</b>	Apply within 5 minutes at 20 °C.
<b>Drying time:</b>	16 – 30 minutes
<b>Sanding:</b>	Hand sanding (dry): P120 – P320. Machine sanding (dry): P120-320
<b>General notes:</b>	Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C.
<b>Storage:</b>	Store in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.
<b>Shelf life:</b>	12 months

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.