

Product information

Product description:	SOLL MAT – a special additive which allows coat matting and obtaining a surface “without gloss”. This effect is obtained by mixing the paste with any type of paint so the surface will not be shinny. Dosage: from 10 % to 40 % of the weight of the coat, depending on the final degree of the “matting” wanted.	
Usage:	Stir thoroughly before use.	
Mixing ratio:		
Surface:	Quantity of matting agent / 1 l:	Loss gloss level:
1) Cellulose topcoat	0 – 250 g	to about 50 %
2) Synthetic topcoat	0 – 350 g	to about 50 %
3) High gloss polyurethane paint	0 – 400 g	to about 50 %
4) Synthetic paint heated in the oven (120 °C).	0 – 250 g	to about 50 %
Chemical and physical characteristics:		
Form:	Liquid	
Colour:	Colourless	
Specific weight:	0,982 g/cm ³	
Auto ignition temperature:	> 200°C	
Solubility in water:	Very poor	
Packing:	1 l	
Storage and shelf life:	Store in the original, unopened package in a cool, dry place, away from sources of ignition and heat. Avoid sunlight. Shelf life: 12 months, at 20 °C temperature.	
Notes:	<p>The above information and our technical indications (both verbal and written or resulting from test), in particular those that regard the applications and uses of our products, correspond to our best knowledge and experience; however, they do not constitute our warranty relative to final results or our responsibility deriving from any juridical relationship whatsoever.</p> <p>In fact, considering the multiplicity of materials, supports, handling and storage conditions, as well as the conditions of production and utilization, the user, in function of his specific circumstances of use, must always preventively verify all the information and instructions reported above.</p> <p>No assertion contained in this publication is to be considered authorization or suggestion to violate any industrial property rights of third parties.</p>	