

SECTION 1: Identification of the substance / mixture and company identification

1.1 Product ID: SILICONE REMOVER SOLL SIL
Art. No. SIL 1; SIL 5

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Identified uses: silicone remover
Advices against uses: not specified

1.3 Data of the supplier Safety Data Sheet:

Manufacturer: UAB HELVINA
Parko str. 96, Ramučiai
LT-54464 Kaunas district
Lithuania
Tel.: +370 37308901 / Fax: +370 37308902
E-mail: info@helvina.lt / www.helvina.lt

1.4 Emergency telephone number:

Poison control and information office: Tel.: +370 5 236 2052 or +370 687 53378

SECTION 2: Hazard identification**2.1 Classification of the substance or mixture**

Classification 67/548/EEC

F; R11

Xn: R65

R66

R67

N:R51/53

Classification 1272/2008

Flam. Liq. 2; H225

Asp. Tox. 1; H304

STOT SE 3; H336

Aquatic Chronic 2; H411

Hazard to human health

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

Environmental hazards

Toxic to aquatic life with long lasting effects.

Physical/chemical hazards

Flammable liquid and vapour.

2.2 Label elements:**Pictogram(s):**

Signal word: **Danger**

Hazard statements:

H225 – Highly flammable liquid and vapour.

H304 – May be fatal if swallowed and enters airways.

H336 – May cause drowsiness or dizziness.

H411 – Toxic to aquatic life with long lasting effects.

EUH066 – Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 – Keep away from heat / sparks / open flames / hot surfaces – No smoking.

P273 – Avoid release to the environment.

P280 – Wear protective gloves / protective clothing / eye protection / face protection.

P302 + P352 – IF ON SKIN: Wash with soap and water.

P304 + P340 – IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Contains: Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclic (EINECS: 920-750-0); cyclohexane (CAS: 110-82-7), hexane (CAS: 110-54-3)

2.3 Other hazards:

No other hazards.

No information on the fulfilment of the criteria for PBT or vPvB in accordance with Annex XIII of the REACH Regulation. Appropriate studies have not been conducted.











SECTION 3: Composition / information on ingredients





3.1 Substances:

Not applicable.

3.2 Mixtures:

Hazardous ingredients:

Product identification	Content %	Classification 67/548/EEC	CLP classification	
			Hazard class and category codes	Phrases codes indicating type of hazard
Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclic CAS: - EINECS: 920-750-0 Index no: - <u>REACH no:</u> 01-2119473851-33-XXXX	90 – 100	 F; R11  Xn: R65 R66 R67  N:R51/53	Flam. Liq. 2 Asp. Tox. 1 STOT SE 3 Aquatic Chronic 2	H225 H304 H336 H411
Hydrocarbons, C9, aromatics CAS: - EINECS: 918-668-5 Index no: - <u>REACH no:</u> 01-2119455851-35-XXXX	1 – 6	R10  Xn: R65  Xi: R37  N:R51/53 R66 R67	Flam. Liq. 3 Asp. Tox. 1 STOT SE 3 Aquatic Chronic 2	H226 H304 H335 H336 H411
Hydrocarbons C7-C9 contains:				
Cyclohexane CAS: 110-82-7 EINECS: 203-806-2 Index no: 601-017-00-1 <u>REACH no:</u> substance is subject to the transitional period	<2	 F; R11  Xn; R65  Xi; R38 R67  N; R50/53	Flam. Liq. 2 Asp. Tox. 1 STOT SE 3 Skin Irrit. 2 Aquatic Acute 1 Aquatic Chronic 1	H225 H304 H336 H315 H400 H410

<p>Hexane CAS: 110-54-3 EINECS: 203-777-6 Index no: 601-037-00-0 REACH no: substance is subject to the transitional period</p>	<3	 F; R11 Repr. Kat. 3; R62  Xn; R65; R48/20  Xi; R38 R67  N; R51/53	<p>Flam. Liq. 2 Asp. Tox. 1 Rerp.2 STOT SE 3 STOT RE 2 Skin Irrit. 2 Aquatic Chronic 2</p>	<p>H225 H304 H361f H336 H373 H315 H411</p>
--	----	--	--	--

Full text of the R and H phrases provided in section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

IF ON SKIN:

Wash contaminated skin with soap and water, rinse with water. If skin irritation or a rash occurs: contact a doctor.

IF IN EYES:

Rinse with plenty of water for about 15 minutes, holding the eyelids wide open. Avoid strong stream of water - risk of cornea damage, contact a doctor.

IF INHALED:

In case of dizziness or nausea remove victim to fresh air, call a doctor if there is no rapid improvement.

IF SWALLOWED:

Do NOT induce vomiting. Get immediate medical advice / attention. Do not give anything by mouth to an unconscious person.

4.2 The most important symptoms and effects, both acute and delayed:

Contact with skin: possible irritation, redness, dryness, cracking.

Contact with eyes: slight irritation in the case of direct contact.

Respiratory system: irritation of nasal mucosa, throat and further parts of respiratory system, may depress central nervous system. Symptoms include headache, dizziness, drowsiness, weakness.

Gastrointestinal tract: chemical irritation of oral cavity, throat and further parts of gastrointestinal tract. After absorption may experience symptoms of food poisoning, abdominal pain, dizziness, nausea and vomiting. Ingestion can lead to aspiration into the lungs and cause chemical pneumonia.

4.3 Indications of any immediate medical attention and special treatment needed:

The decision on how to proceed take the doctor after examination of injured.

SECTION 5: Fire fighting measures

5.1 Extinguishing media:

Appropriate extinguishing media: alcohol-resistant foam or dry powder (A,B,C), carbon dioxide (CO₂ type extinguisher), sand or soil, water fog. Use suitable fire extinguishing methods depending on the conditions.

Inappropriate extinguishing media: Strong stream of water.

5.2 Special hazards arising from the substance or mixture:

During a fire, high temperatures can cause release of toxic decomposition products which contain inter alia: carbon oxides, nitrogen oxides. Vapours are able to form explosive mixtures with air. Heavier than air they accumulate in depressions or in lower parts of the room – can cause the phenomenon of flashback.

5.3 Advice for firefighters:

Cool containers situated in zone of fire by spraying water, if possible, remove from the danger zone. In case of fire in a closed room wear protective clothing and self-contained breathing apparatus. Do not allow to get through the extinguishing water to surface water, groundwater and sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For persons not being the members of aid giving staff: inform the appropriate service. Remove from the danger zone people not involved in the liquidation of accident. Remove all possible sources of ignition.

For persons giving aid: Ensure proper ventilation, use protective gloves, protective shoes, protective clothing. Use protective glasses. Do not breathe vapours.

6.2 Environmental precautions:

Prevent from spreading and leakage into sewage system and water reservoir. In case of inability inform the local authorities to provide protection.

6.3 Methods and materials for containment and cleaning up:

Prevent from spreading and remove by gathering on absorbent material (sand, sawdust, diatomaceous soil, universal absorbent). Contaminated material put in properly labelled containers for disposal in accordance with applicable regulations.

6.4 Reference to other sections

Disposal considerations – see section 13 of the Safety Data Sheet.

Personal protection measures – see section 8 of the Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Use only in well ventilated area. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid spilling. Avoid breathing vapours. Do not allow to exceed the NDS value in the workplace for the product components. Avoid sources of ignition, heat, hot surfaces and open flames. Apply measures against electrostatic charges – appropriate neutralization and protective earthing during e.g. transferring contents of the containers. It is recommended to wear anti-static clothing and footwear during handling the product. Floor of the room where product is stored or used should be made of electrically conductive materials. Make sure if the electric lighting and wiring are working properly and do not constitute a potential source of ignition. Do not use cutting tools that cause sparks. Avoid inhalation of vapours / aerosols. Work in accordance with the principles of health and safety: do not eat and drink, do not smoke in the workplace, wash hands after use, remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a cool (storage temperature 5°C - 30°C), dry, well-ventilated room. Store in properly labelled and tightly closed original container. Avoid direct sunlight and sources of heat, hot surfaces and open flames. If repackaging is necessary, make sure that the new packaging is suitable for the type of product. After opening close tightly containers and set upright to prevent leakage of the product. Do not store near oxidizing agents, strongly alkaline, strongly acidic products and combustible materials.

7.3 Special end use(s): silicone remover

SECTION 8: Exposure control/personal protection

8.1 Control parameters:

Components, for which exposure standards are in force.

Name / type of component	NDS	NDSch	NDSP
	mg/m ³		
Cyclohexane	300	1000	-
Hexane	72	-	-

Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclic

DNEL for workers, chronic exposure through the skin: 773mg/kg/day

DNEL for workers, chronic exposure through inhalation: 2035mg/m³

DNEL for consumer, chronic exposure through the skin: 699mg/kg/day

DNEL for consumer, chronic exposure through inhalation: 608mg/m³

DNEL for consumer, chronic exposure if swallowed: 699mg/kg/day

Hydrocarbons, C9, aromatics

DNEL for workers, prolonged exposure through the skin (systemic effects): 25mg/kg mc/day

DNEL for workers, prolonged exposure through inhalation (systemic effects): 150mg/m³
 DNEL for consumer, prolonged exposure through the skin (systemic effects): 32mg/kg mc/day
 DNEL for consumer, prolonged exposure through inhalation (systemic effects): 150mg/m³
 DNEL for consumer, prolonged exposure if swallowed (systemic effects): 11mg/kg mc/day

8.2 Exposure control:

Appropriate technical control measures: use of general ventilation of the room is recommended.

Individual protection measures, such as personal protective equipment:**Eye or face protection:**

Wear protective glasses or protective mask (in accordance with EN 166).

Skin protection:**Hand protection:**

Use protective gloves resistant to chemicals, made of viton, 0,7 mm thick, penetration time > 480 min or nitrile rubber, 0,4 mm thick, penetration time > 30 min in accordance to EN-PN 374:2005.

The material from which the gloves are made:

Choice of suitable gloves depends not only on the material, but also on the brand and quality that depend on manufacturer. Resistance of the material from which gloves are made can be determined after testing. The exact time of the destruction of the protective gloves must be determined by the manufacturer.

Other:

Wear protective clothing working – wash regularly.

Respiratory system protection:

Avoid breathing vapours. In case of exceeding the NDS value in the workplace use personal respiratory system protection – mask or half mask with filter and universal or A type vapour absorber (class 1, 2 or 3) in accordance with EN 141.

Thermal hazards:

Not applicable.

Control of environmental exposure

Do not allow to spread in the environment and leakage to sewage system and watercourses.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Physical state	liquid
Colour	colourless
Odour	slight
Odour threshold	not specified
pH	not applicable
Melting point (range)	not applicable
Boiling point (range)	90 – 165°C
Flash point	<10°C
Ignition temperature	not specified
Evaporation rate (n-butyl acetate=1)	1,4

Flammability (solid, gas)	not applicable
Bottom explosion limit	0,6% vol.
Top explosive limit	7,0% vol.
Vapour pressure (20°C)	2kPa
Relative vapour density (air=1)	>1 at 101kPa
Solubility in water	very weak
N-octanol / water division ratio	not specified
Autoignition point	>200 °C
Breakdown point	not specified
Kinematic viscosity at 20°C	0,5 - 1,5mm ² /s
Explosive properties	not applicable
Oxidizing properties	not applicable

9.2 Other information:

No additional test results.

SECTION 10: Stability and reactivity**10.1 Reactivity:**

Unknown.

10.2 Chemical stability:

Product remains stable under normal use, storage and transport conditions.

10.3 Possibility of hazardous reactions:

None.

10.4 Conditions to be avoided:

Avoid high temperature, direct sunlight, hot surfaces and open flames.

10.5 Incompatible materials:

Strong oxidizing agents.

10.6 Hazardous decomposition products:

As a result of high temperatures toxic gases are generated – carbon oxides.

SECTION 11: Toxicological information**11.1 Information on toxicological effects:**

a) acute toxicity: does not show

Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclic:

LD₅₀ (rat; orally) >5000mg/kg

LC₅₀ (rat; inhalation) >23,3mg/l/4h

LD₅₀ (rabbit; skin) >2800mg/kg

Hydrocarbons, C9, aromatics:

LD₅₀ (rat; orally) 3592mg/kg

LC₅₀ (rat; inhalation) >6193mg/m³/4h

LD₅₀ (skin) >3160mg/kg

b) irritating effect: does not show

c) caustic effect: does not show

d) allergenic effects: does not show

e) toxicity for repeated exposure: May cause drowsiness or dizziness

f) cancerogenity: does not show

- g) mutagenity: does not show
 h) harmful effect on reproduction: does not show

Information on likely routes of exposure:

Contact with skin: possible irritation, redness, dryness, cracking.

Contact with eyes: slight irritation in the case of direct contact.

Respiratory system: irritation of nasal mucosa, throat and further parts of respiratory system, may depress central nervous system. Symptoms include headache, dizziness, drowsiness, weakness.

Gastrointestinal tract: chemical irritation of oral cavity, throat and further parts of gastrointestinal tract. After absorption may experience symptoms of food poisoning, abdominal pain, dizziness, nausea and vomiting. Ingestion can lead to aspiration into the lungs and cause chemical pneumonia.

Delayed and immediate and chronic effects from short-and long-term exposure:

No data.

The effects of the interaction:

No data.

SECTION 12: Ecological information

Detailed studies of the environmental effects of the mixture were not carried out. Harmful to aquatic life with long lasting effects. Do not allow to leakage to ground water sewage system and watercourses.

12.1 Toxicity:**Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclic:**

LL ₅₀ – fish (<i>Oncorhynchus mykiss</i>)	>13,4mg/l, 96h
EL ₅₀ – invertebrates (<i>Daphnia</i>)	3mg/l (48h)
NOEC – invertebrates	0,17mg/l, 21 days
LOEC – invertebrates	0,32mg/l, 21 days
NOELR – algae (<i>Pseudokirchineriella subcapitata</i>)	10mg/l, 72h
EL ₅₀ – algae (<i>Pseudokirchineriella subcapitata</i>)	10-30mg/l, 72h

Hydrocarbons, C9, aromatics:

LL ₅₀ – fish (<i>Oncorhynchus mykiss</i>)	9,2 mg/l, 96h
EL ₅₀ – invertebrates (<i>Daphnia magna</i>)	3,2 mg/l, 48h
E _r L ₅₀ – algae (<i>Pseudokirchneriella subspicatus</i>)	2,9 mg/l, 72h
NOER – algae (<i>Pseudokirchneriella subspicatus</i>)	1 mg/l, 72h

12.2 Persistence and degradability:**Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclic**

Product undergoes rapid biodegradation

Hydrolysis: conversion as a result of hydrolysis should not be significant.

Photolysis: conversion as a result of photolysis should not be significant.

Atmospheric oxidation: rapidly degraded in air.

Hydrocarbons, C9, aromatics: product undergoes rapid biodegradation

Hydrolysis: conversion as a result of hydrolysis should not be significant.

Photolysis: conversion as a result of photolysis should not be significant.

Atmospheric oxidation: rapidly degraded in air.

12.3 Bioaccumulative potential:

No data.

12.4 Mobility in soil:**Hydrocarbons C7-C9, n-alkanes, iso-alkanes, cyclic**

Very easily volatile; evaporates quickly. Sedimentation in sediments and solids in the wastewater is not expected.

12.5 Results of PBT and vPvB assessment:

No data.

12.6 Other adverse effects:

No data.

SECTION 13: Disposal considerations**13.1 Waste treatment methods:**

Disposable containers and waste must be disposed by authorized firm. Disposal procedure should be agreed with area competent department of environmental protection. Rest of product store in original containers. Dispose in accordance with applicable regulations. Empty containers must be disposed in accordance with applicable regulations or deliver to suitable garbage dump.

SECTION 14: Transport information

14.1 UN number (ONZ number): 1263

14.2 UN proper shipping name: PAINT OR PAINT RELATED MATERIAL

14.3 Transport hazard class(es): 3

14.4 Packaging group: II

14.5 Environmental hazards: yes

14.6 Special precautions for user: always transport in closed containers that are upright, labelled and secured.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 Convention and the IBC Code: no information.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

* Regulation (EC) No 1907/2006 of THE EUROPEAN PARLIAMENT AND THE COUNCIL of 18 December 2006 Concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), with subsequent amendments.

* Commission Regulation (EU) No. 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of THE EUROPEAN PARLIAMENT AND THE COUNCIL Concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).

* Regulation (EC) No 1272/2008 (CLP) (Article 55, Annex VI, Table 3.2) of THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, with subsequent amendments.

* Council Directive No. 75/442/EEC On waste and Council Directive No. 91/689/EEC On hazardous waste. Commission Decision No 2000/532/EC of 3 May 2000, stating the list of waste, OJ No. L 226 / 3, 6 September 2000, along with changing decisions.

15.2 Chemical safety assessment:

No chemical safety assessment for the substances, and the mixture.

SECTION 16: Other information**R and H phrases:**

R10 – Flammable.

R11 – Highly flammable.

R37 – Irritating to respiratory system.

R38 – Irritating to skin.

R48/20 – Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53 – Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 – Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62 – Possible risk of impaired fertility.

R65 – Harmful: may cause lung damage if swallowed.

R66 – Repeated exposure may cause skin dryness or cracking.

R67 – Vapours may cause drowsiness and dizziness.

H225 – Highly flammable liquid and vapour.

H226 – Flammable liquid and vapour.

H304 – May be fatal if swallowed and enters airways.

H315 – Causes skin irritation.

H335 – May cause respiratory irritation.

H336 – May cause drowsiness or dizziness.

H361f – Possible risk of impaired fertility.

H373 – May cause damage to organs through prolonged or repeated exposure.

H400 – Very toxic to aquatic life.

H410 – Very toxic to aquatic life with long lasting effects.

H411 – Toxic to aquatic life with long lasting effects.

Explanation of the abbreviations, acronyms and symbols used in the Safety Data Sheet:

F – Highly flammable

Xn – Harmful

Xi – Irritant

N – Dangerous for the environment

Flam. Liq. 2 – Liquid, flammable substances, category 2

Flam. Liq. 3 – Liquid, flammable substances, category 3

Asp. Tox. 1 – Aspiration hazard, category 1

Repr. 2 – Reproductive toxicity, category 2

Skin Irrit. 2 – Irritating effect on skin, category 2

STOT SE 3 – Toxic effect on target organs – single exposure, category 3

STOT RE 2 – Specific target organ toxicity – repeated exposure, category 2

Aquatic Acute 1 – Hazardous to the aquatic environment - acute hazard, category 1

Aquatic Chronic 1 – Hazardous to the aquatic environment - chronic hazard, category 1

Aquatic Chronic 2 – Hazardous to the aquatic environment - chronic hazard, category 2

NDS – Maximum permissible concentration of substances in the workplace

NDSP – Maximum permissible ceiling concentration

NDSch – Maximum permissible instantaneous concentration

Training:

Before starting handling the product, workers must undergo obligatorily occupational health and safety training because of presence of chemicals in the workplace. Perform, document and familiarize employees with the results of risk assessment in the workplace due to the presence of chemical agents.

The information of this Material Safety Data Sheet is based on the present state of knowledge and on current EU and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this Material Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.